



TRAFFIC CONTROL DEVICES  
MANUAL FOR WORK ZONES

Section:

SIGNS

Subject:

SIGN DESCRIPTION  
REGULATORY

CODE	SIGN	SIZE (cm)	COLOUR MESSAGE	BGRD	DESCRIPTION	SPEC
RA-1		75 x 75	White	Red	<b>Stop</b> Indicates to drivers facing the sign to stop completely and not to proceed until it is safe to do so.	245S
RA-2		75x75x 75	Red	White	<b>Yield</b> Indicates to drivers facing the sign to yield the right of way, stopping if necessary before entering the intersection area, and not proceed until it is safe to do so.	245S
RB-1		60x75	Black	White	<b>Maximum Speed</b> Indicates to motorists the maximum legal vehicle speed which is permitted on the roadway section indicated by the presence of the signs.  The maximum speed in kilometres per hour, as established by law, and shown in multiples of 10 km/h.	245S
RB-5		60x75	Black	White	<b>Maximum Speed Ahead</b> Indicates to motorists that they are approaching a section of roadway upon which the statutory speed limit is reduced. Is always followed by the Maximum Speed sign (RB-1) at a distance of not less than 90 nor more than 150 m.	245S
RB-11R/L		60x60	Black	White	<b>No Right Turn (Left)</b>	240
RB-16		60x60	Black	White	<b>No U Turns</b>	240
RB-23		75x75	Red	White	<b>Do Not Enter</b>	245S

Section:

SIGNS

Subject:

SIGN DESCRIPTION  
REGULATORY

CODE	SIGN	SIZE (cm)	COLOUR MESSAGE BGRD	DESCRIPTION	SPEC	
RB-24		60x75	Black	White	<b>Two Way Traffic</b> Installed to advise motorists they are about to enter a two way roadway.  Placed on each side of the roadway at the beginning of the section where two way traffic is permitted.	245S
RB-25		60x75	Black	White	<b>Keep Right</b> Installed in the gore point at the transition from two lane to four lane highway and face the motorist travelling along the two lanes highway towards the four lane highway.	245S
RB-31		75x75	Black	White	<b>Do Not Pass</b> Installed to warn motorists that passing would be hazardous due to lane closures or windrowed material.	245S
RB-32		75x75	Black	White	<b>Passing Permitted</b> May be installed at the end of a no passing zone where a Do Not Pass sign has been installed at the beginning.	240
RB-61		75x75	Black	White	<b>Truck Route</b>	245S
RB-62		75x75	Black	White	<b>Truck Prohibition</b>	245S
RB-63		60x60	Black	White	<b>Weight Limit Control</b>	245S
RB-151		60x60	Black	White	<b>Rural Parking Control</b>	240
RB-155		60x60	Black	White	<b>Rural Stopping Control</b>	240

Section:

SIGNS

Subject:

SIGN DESCRIPTION  
REGULATORY

CODE	SIGN	SIZE (cm)	COLOUR MESSAGE BGRD	DESCRIPTION	SPEC
RC-4R/L		60x75	Black	White	<b>Stop Line Right (Left)</b> 240
RS-25		240x120	Black	White	<b>Highway Closed Ahead</b> Installed to indicate to the motorist that the road is closed due to a hazardous condition. 245S
RS-26		120x75	Black	White	<b>Road Closed</b> Installed where a road is closed entirely to public traffic. 245S
RS-27		150x75	Black	White	<b>Road Closed To Thru Traffic</b> Installed where a road is closed entirely to public traffic. 245S
RS-28		240x120	Black	White	<b>Highway ___ Closed ___ km Ahead</b> Should be installed to advise motorists that a certain highway is closed to traffic beyond a certain point. 245S

The route numbers and kilometres can be ordered separately in the form of E Series decals so that the signs can be used at various locations.

Date

2009-08-25

Page

3 of 3