














**TRAFFIC CONTROL DEVICES
MANUAL FOR WORK ZONES**

Section:
SIGNS
Subject:
**SIGN DESCRIPTION
WARNING**

CODE	SIGN	SIZE (cm)	COLOUR MESSAGE BGRD	DESCRIPTION	SPEC
WS-13		90x90	Black Yellow	Gravel Sections	240
WS-16A		35x35x 35	Red Orange	Slow Moving Vehicle (small)	310
WS-16B		75x75x 75	Red Orange	Slow Moving Vehicle (large)	310
WS-18		120x150	Black Yellow	Advisory Exit Speed	245S
WS-21		45x45	Fluorescent	Metal Flags	273
WS-25		75x75	Black Yellow	Broken Pavement	245S

Section:	Subject:
SIGNS	SIGN DESCRIPTION WARNING

CODE	SIGN	SIZE (cm)	COLOUR MESSAGE BGRD	DESCRIPTION	SPEC
WS-30		90x90	Black Yellow	Heavy Truck Haul	245S
WS-53		240x120	Black Yellow	Remember Two Way Traffic Shall be installed to advise motorists that they are on a two way roadway and that the normal rules of the road for two way operation apply. Should be installed 800 m beyond the RB-24 sign (Two Way Traffic Sign) and placed every 3 km thereafter within the work zone. The sign tab Next ___ km (WD-53T) shall indicate the length of two-way traffic to be encountered by the motorists within the work zone.	245S
WS-53T		240x45	Black Yellow	NEXT ___ km Tab	245S
WS-54		270x120	Black Yellow	Highway Closed When Flashing	245S
WS-60		210x120	Black Yellow	Advance Runaway Truck Ramp	245S
WS-61		210x150	Black Yellow	Directional Runaway Truck Ramp	245S
WS-65		75x60	Black Yellow	Vehicle Backs Up	240