SafePace® 625 Variable Messaging Sign

The newest sign to the SafePace lineup, the SafePace 625 speed sign displays driver speed and includes a "Slow Down" message that can be displayed to drivers who exceed the speed you choose.

Offering a compact, lightweight design and highly visible full size 15" led digits, the SafePace 625 is the ideal sign when you want to show drivers their speed with the added feature of programmable slow down messaging. Optional universal mounting and solar or battery power make the SafePace 625 a versatile option for portable, autonomous traffic calming.



625 Specifications

Digit Size	15"
Height	28"
Weight	55 lbs
24/7, 365 Scheduling	✓
Data Collection	✓
Solar Compatibility	✓
Battery Operated	
Universal Mounting	
Cloud Compatibility	✓
Trailer Compatibility	✓
Dolly Compatibility	
Hitch Compatibility	
Warranty	2 Years

Features

Choice of faceplate colors available

Compact design is **30% smaller** than full size SafePace sign without compromising on features or visibility

Six inch LED **Slow Down messaging alerts drivers** who are exceeding the speed limit of your choice

Includes two **integrated flashing speed violator strobes** to further alert speeding drivers

Unique light enhancing, anti glare lens system provides **brilliant visibility** even in poor lighting conditions

Ultra low power consumption includes the **most powerefficient** radar technology available and optional solar power

Optional battery power allows for **weeks of autonomous operation** with normal usage

High strength aluminum sign face and individual optical lenses protect against vandalism and theft

Stealth mode allows the sign to **collect baseline traffic data** while speed display appears blank to motorists





Feature	Specifications	
Dimensions		
Digits	15"(h) x 8"(w), 744 LEDs	
Message Matrix	15"(h) x 20.5"(w), 744 LEDs	
Text	Full size: Letters 6.0"(h) spell "YOUR SPEED" fixed message, 2 lines Compact size: Letters 4.0" (h) spell "YOUR SPEED" fixed message, 1line	
Unit alone	21.5"(h) x 26"(w) x 3.5"(d)	
Unit with "YOUR SPEED" sign mounted	Full size: 40.0"(h) x 30.0"(w) x 3.5"(d) Compact size: 28.0"(h) x 28.0"(w) x 3.5"(d)	
Sign Weight (unit alone, without "YOUR SPEED" sign)		
AC Powered	24 lbs	
4 cell battery powered model	24 lbs (not including batteries)	
Solar powered model	24 lbs (not including solar panel or bracket)	
General Specifications		
Operating Temperatures F (C):	-40° (-40°) to 185° (85°)	
Speed Units	Miles per hour (mph) or Kilometers per hour (km/h)	
Faceplate	Yellow or white high-Intensity prismatic reflective sheeting on sign face with black colored text. MUTCD approved colors and format	

Feature	Specifications	
Bashplate	Aluminum, 0.1875"	
Communications	Bluetooth (standard) GSM/GPRS (optional, for use with SafePace Cloud)	
Programming	SafePace Pro sign management software SafePace Cloud remote sign management 24/7 365 day unlimited programming and scheduling	
Power Options (Electrical Specifications)		
AC power input	100~240 V AC	
DC power input	12 V DC	
Solar panel options	950W, 90W	
Radar		
Internal	Doppler (FCC approved)	
Radar RF out	5 mW maximum	
Radar f-center	24.125 GHz +/- 25 MHz	
Pickup distance	Up to 1,200 feet	
Beam	11° × 11°, Linear polarization	
Display		
	Display	
LEDs	Display 796	
LEDs Digits		
	796 744 Amber, 15°, 5 mm, luminous Intensity	
Digits	796 744 Amber, 15°, 5 mm, luminous Intensity (5,000 – 12,000 mcd/LED) 52 White, 15°, 5 mm, luminous intensity	
Digits Speed Violator Strobe	796 744 Amber, 15°, 5 mm, luminous Intensity (5,000 – 12,000 mcd/LED) 52 White, 15°, 5 mm, luminous intensity (18,000 – 28,000 mcd/LED)	
Digits Speed Violator Strobe Optical Lenses	796 744 Amber, 15°, 5 mm, luminous Intensity (5,000 – 12,000 mcd/LED) 52 White, 15°, 5 mm, luminous intensity (18,000 – 28,000 mcd/LED) 796 2 sensors and automatic brightness	
Digits Speed Violator Strobe Optical Lenses	796 744 Amber, 15°, 5 mm, luminous Intensity (5,000 – 12,000 mcd/LED) 52 White, 15°, 5 mm, luminous intensity (18,000 – 28,000 mcd/LED) 796 2 sensors and automatic brightness control	
Digits Speed Violator Strobe Optical Lenses Ambient Light Sensors	796 744 Amber, 15°, 5 mm, luminous Intensity (5,000 – 12,000 mcd/LED) 52 White, 15°, 5 mm, luminous intensity (18,000 – 28,000 mcd/LED) 796 2 sensors and automatic brightness control Enclosure 12/14 gauge aluminum, flat black powder coated front for reduced glare and maximum contrast; light gray powder	
Digits Speed Violator Strobe Optical Lenses Ambient Light Sensors Construction	796 744 Amber, 15°, 5 mm, luminous Intensity (5,000 – 12,000 mcd/LED) 52 White, 15°, 5 mm, luminous intensity (18,000 – 28,000 mcd/LED) 796 2 sensors and automatic brightness control Enclosure 12/14 gauge aluminum, flat black powder coated front for reduced glare and maximum contrast; light gray powder coated body to minimize heat absorption Weatherproof, NEMA 4X-12, IP65 level compliant	
Digits Speed Violator Strobe Optical Lenses Ambient Light Sensors Construction	796 744 Amber, 15°, 5 mm, luminous Intensity (5,000 – 12,000 mcd/LED) 52 White, 15°, 5 mm, luminous intensity (18,000 – 28,000 mcd/LED) 796 2 sensors and automatic brightness control Enclosure 12/14 gauge aluminum, flat black powder coated front for reduced glare and maximum contrast; light gray powder coated body to minimize heat absorption Weatherproof, NEMA 4X-12, IP65 level compliant Non-sealed and ventilated	

